



DIVYOL WOT SPECIALITY MINERAL OILS
(Paraffin Oils/ White Mineral Oils)

| Test Description | Test Method | Specification Limits | | | | | | | | |
|-----------------------------|-------------|--|---------------|---------------|----------------|---------------|----------------|----------------|----------------|----------------|
| | | DIVYOL WOT 60 | DIVYOL WOT 70 | DIVYOL WOT 80 | DIVYOL WOT 100 | DIVYOL WOT150 | DIVYOL WOT 180 | DIVYOL WOT 250 | DIVYOL WOT 350 | DIVYOL WOT 500 |
| Appearance | Visual | Transparent clear, colorless, odorless liquid free from suspended impurities | | | | | | | | |
| Colour, Say bolt | ASTM D 156 | +30 | | | | | | | | |
| Density @ 25 °C, gm/ml | ASTM D 1298 | > 0.810 | > 0.820 | > 0.822 | >0.828 | >0.830 | >0.835 | >0.835 | >0.850 | >0.860 |
| Kin. Viscosity @ 40 °C, cSt | ASTM D 445 | 7 - 11 | 11 - 14 | 14 - 17 | 19-23 | 27 - 33 | 30 - 35 | 36 - 45 | 68 - 72 | 80 - 85 |
| Flash Point °C min | ASTM D 92 | 145 | 150 | 160 | 180 | 180 | 190 | 190 | 200 | 220 |
| Pour Point, °C, max | ASTM D 97 | -15 | -15 | -15 | -12 | -12 | - 12 | - 12 | - 12 | - 12 |

Health & Safety: Refer MSDS