Adding Miles to Mileage

gandhar
Stay Ahead



Automotive Oils

divyol
solutions within solutions

CONTENTS

AGRICULTURAL OIL (AGRIL)	
Divyol Triller X	7 – 12
Divyol Pso 20w40	13 – 18
Divyol Unitraxx (Utto)	19 – 24
AUTOMOTIVE GEAR OIL (AGO)	
Divyol Spin EP 80w90 – GL4	25 – 30
Divyol Spin EP 90 - GL4	31 – 36
Divyol Spin EP 140 – GL4	37 – 42
Divyol Spin SXD 75W90 – GL5	43 – 48
Divyol Spin SXP 75W90 – GL4	49 – 54
Divyol Spin XD 80w90 – GL5	55 – 60
Divyol Spin XD 85W140 – GL5	61 – 66
Divyol Spin XD 90 – GL5	67 – 72
AUTOMOTIVE TRANSMISSION FLUIDS	
Divyol TQX 2 - Dexron II G	73 – 78
DIVYOL TQX 3 - DEXRON III E	79 – 84
Divyol TQX 1 Type ‘A’ Suffix ‘A’	85 – 90

CONTENTS

CNG OIL (GEO)	
Divyol ECO4 SAE 20W40	91 – 96
Divyol ECO4 SAE 20W50	97 – 102
DIVYOL GASOL 30	103 – 108
DIVYOL GASOL 40	109 – 114
CONSTRUCTION EQUIPMENT OIL (CEO)	
Divyol Entro HVI 10 W	115 – 120
Divyol Entro HVI 32	121 – 126
Divyol Entro HVI 46	127 – 132
Divyol Entro HVI 68	133 – 138
Divyol Entro HVI 100	139 – 144
Divyol Hydraulic Oil 10W	145 – 150
Divyol Hydraulic Oil 30W	151 – 156
Divyol Power Trans C3/C4 SAE 10	157 – 162
Divyol Power Trans C3/C4 SAE 30	163 – 168

CONTENTS

DIESEL ENGINE OIL (DEO)

Divyol Disol C 20W40 – API CD+	169 – 174
Divyol Disol C 20W50 - API CD+	175 – 180
DIVYOL DISOL C 30 – API CD+	181 – 186
DIVYOL DISOL C 40 – API CD+	187 – 192
DIVYOL DISOL C 50 – API CD+	193 – 198
DIVYOL DISOL CG4 15W40	199 – 204
Divyol Disol D 20W40	205 – 210
Divyol Disol C 30 – API CF	211 – 216
Divyol Disol D 40 – API CF	217 – 222
Divyol Disol D 50 – API CF	223 – 228
Divyol Disol EXV 5W40	229 – 234
Divyol Disol HXV 15W40	235 – 240
Divyol Disol LXV 15W40	241 – 246
Divyol Disol SXV 15W40	247 – 252
Divyol Disol TC 15W40	253 – 258
Divyol TRACXX 20W40	259 – 264
Divyol Disol Turbo 15W40	265 – 270
Divyol Disol XV 15W40	271 – 276
Divyol Red Plus 20W40	277 – 282

CONTENTS

DIESELEXHAUSTFLUID	
DIVYOL ECO BLUE	283 – 288
HYDRAULIC TRANSMISSION OIL	
DIVYOL HYTRANS G SAE 10W	289 – 294
DIVYOL HYTRANS G SAE 30W	295 – 300
MOTOR CYCLE OIL (MCO)	
Divyol Spin 4T 20W40	301 – 306
Divyol Spin 4T Advance 10W30	307 – 312
Divyol Spin 4T Scool 10W30	313 – 318
DIVYOL SPIN 4T ZOOM 20W40	319 – 324
Divyol Spin Q3 20W40	325 – 330
DIVYOL SPIN Q4 20W40	331 – 336
Divyol Spin Q5 20W50	337 – 342
DIVYOL SPIN X2 20W50	343 – 348
DIVYOL SPIN X3 10W30	349 – 354
DIVYOL SPIN X4 20W40	355 – 360
DIVYOL SPIN X5 15W50	361 – 366
DIVYOL SWING SHOCKER OIL	367 – 372

CONTENTS

OUT BOARD MOTOR OIL	
DIVYOL GONDOLA X2	373 – 378
DIVYOL GONDOLA X3	379 – 384
PASSENGER CAR MOTOR OIL (PCMO)	
Divyol Spectro AX 5W40 SN	385 – 390
Divyol Spectro 5W30 SN	391 – 396
Divyol Spectro LX 10w30 SN	397 – 402
Divyol Spectro SX 20w50 SN	403 – 408
Divyol Spectro VX 10w40 SN	409 – 414
THREE WHEELER OILS (TWO)	
Divyol Auto Plus	415 – 420

DIVYOL TRILLER X

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Triller X	
Product description	Power Tiller Oil	
Product type	Agricultural Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97
Flash point	> 200 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL PSO 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Pso 20w40	
Product description	Pump Set Oil	
Product type	Agricultural Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 200 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL UNITRAXX (UTTO)

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Unitraxx (Utto)	
Product description	Agricultural Gear Oil	
Product type	Agricultural Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	10 to 11.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN EP 80W90 – GL4

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Ep 80w90 – Gl4	
Product description	Multi Purpose Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -9°C (ASTM D-97)
Flash point	> 195 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 18 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN EP 90 – GL4

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Ep 90 - Gl4	
Product description	High Perfomace Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 195 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 18 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN EP 140 – GL4

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Ep 140 – Gl4	
Product description	High Perfomace Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 190 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	24 to 35 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN SXD 75W90 – GL5

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Sxd 75w90 – Gl5	
Product description	Heavy Duty Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -33°C (ASTM D-97)
Flash point	> 180 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 16 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN SXP 75W90 – GL4

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Sxp 75w90 – Gl4	
Product description	Multi Purpose Extreme Pressure Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -33°C (ASTM D-97)
Flash point	> 180 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 16 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN XD 80W90 – GL5

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Xd 80w90 – Gl5	
Product description	Heavy Duty Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -9°C (ASTM D-97)
Flash point	> 195 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 18 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN XD 85W140 – GL5

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Xd 85w140 – Gl5	
Product description	Multi Purpose Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 190 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	24 to 35 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN XD 90 – GL5

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Xd 90 – Gl5	
Product description	Heavy Duty Gear Oil	
Product type	Automotive Gear Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 195 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	14 to 18 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL TQX 2 - DEXRON II G

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Tqx 2 - Dexron II G	
Product description	Gear Box Fluids	
Product type	Automotive Transmission Fluid	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -39°C (ASTM D-97)
Flash point	> 180 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	7 to 8.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL TQX 3 - DEXRON III E

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Tqx 3 - Dexron III E	
Product description	Gear Box Fluids	
Product type	Automotive Transmission Fluid	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -39°C (ASTM D-97)
Flash point	> 180 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	6.8 to 8.4 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL TQX 1 TYPE 'A' SUFFIX 'A'

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Tqx 1 Type 'A' Suffix 'A'	
Product description	Gear Box Fluids	
Product type	Automotive Transmission Fluid	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -39°C (ASTM D-97)
Flash point	> 180 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	7 to 8.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ECO4 SAE 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Eco4 Sae 20w40	
Product description	High Perfomance Multi Grade Diesel Engine Oil	
Product type	Cng Oil/Gas Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -9°C (ASTM D-97)
Flash point	> 220 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ECO4 SAE 20W50

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Eco4 Sae 20w50	
Product description	Premium Quality Gas Engine Oil	
Product type	Cng Oil/Gas Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -9°C (ASTM D-97)
Flash point	> 220 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL GASOL 30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL GASOL 30	
Product description	Premium Quality Gas Engine Oil	
Product type	Cng Oil/Gas Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 220 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL GASOL 40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL GASOL 40	
Product description	Premium Quality Gas Engine Oil	
Product type	CNG Oil/Gas Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 220 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ENTRO HVI 10 W

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Entro HVI 10 W	
Product description	High Viscosity Index Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -15°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	10 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ENTRO HVI 32

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Entro HVI 32	
Product description	High Viscosity Index Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -15°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	32.00 (ASTM D 445) (TYPICAL VALUE)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ENTRO HVI 46

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Entro HVI 46	
Product description	High Viscosity Index Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -39°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	46.00 cst (ASTM D 445) (TYPICAL VALUE)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ENTRO HVI 68

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Entro HVI 68	
Product description	High Viscosity Index Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Water White
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -36°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	68.00 cst (ASTM D 445) (TYPICAL VALUE)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ENTRO HVI 100

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Entro HVI 100	
Product description	High Viscosity Index Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Water White
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -9°C (ASTM D-97)
Flash point	> 225 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	100 cst (ASTM D 445) (TYPICAL VALUE)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL HYDRAULIC OIL 10W

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Hydraulic Oil 10W	
Product description	Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Water White
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -18°C (ASTM D-97)
Flash point	> 190 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	5.0 cst (ASTM D 445) (TYPICAL VALUE)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL HYDRAULIC OIL 30W

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Hydraulic Oil 30W	
Product description	Hydraulic Oil	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -15°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	10 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL POWER TRANS C3/C4 SAE 10

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Power Trans C3/C4 SAE 10	
Product description	Hydraulic Tranmsision Fluid	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 190 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	5.6 to 7.4 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL POWER TRANS C3/C4 SAE 30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Power Trans C3/C4 SAE 30	
Product description	Hydraulic Tranmsision Fluid	
Product type	Construction Equipment Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -15°C (ASTM D-97)
Flash point	> 200 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 20W40 – API CD+

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol C 20W40 – API CD+	
Product description	Multigrade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 20W50 – API CD+

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol C 20W50 - API CD+	
Product description	Multipurpose Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 30 – API CD+

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol C 30 – API CD+	
Product description	Multigrade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 40 – API CD+

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol C 40 – API CD+	
Product description	Multigrade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 50 – API CD+

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol C 50 – API CD+	
Product description	Multigrade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL CG4 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL CG4 15W40	
Product description	Advanced Heavy Duty Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL D 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol D 20W40	
Product description	High Perfomance Premium Quality Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL C 30 – API CF

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Disol D 30 – API CF	
Product description	Heavy Duty Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL D 40 – API CF

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL D 40 – API CF	
Product description	Multi Grade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL D 50 – API CF

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL D 50 – API CF	
Product description	Multi Grade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -6°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL EXV 5W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL EXV 5W40	
Product description	High Perfomance Synthetic Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -33°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL HXV 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL HXV 15W40	
Product description	High Perfomance Semi Synthetic Blend Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL LXV 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL LXV 15W40	
Product description	High Perfomance Semi Synthetic Blend Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL SXV 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL SXV 15W40	
Product description	Premium Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL TC 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL TC 15W40	
Product description	High Perfomance Semi Synthetic Blend Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL TRACXX 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL TRACXX 20W40	
Product description	Multi Grade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL TURBO 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL TURBO 15W40	
Product description	High Perfomance Semi Synthetic Blend Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL DISOL XV 15W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL DISOL XV 15W40	
Product description	High Perfomance Synthetic Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL RED PLUS 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL RED PLUS 20W40	
Product description	Multigrade Diesel Engine Oil	
Product type	Diesel Engine Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Automotive	
Formulation & (re)packing of substance & mixtures	Automotive	
Manufacture of substance	Automotive	
Functional fluids	Automotive	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons & Additives	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 195 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density (g/ml)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL ECO BLUE

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Eco Blue	
Product description	Premium Diesel Exhaust Fluid	
Product type	Diesel Exhaust Fluid	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Water White
Odor	Ammonia Cal
Odour threshold	Not available
pH	9.8 to 10.00 %
Pour point	Not Applicable
Flash point	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	6.4 kPa (48 mm Hg) @40°C
Density Solubility (ies)	1.09 g/cm3 @ 20 °C

Solubility (water)	Soluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	100 °C
Kinematic viscosity at 100 °C (210 °F)	Not Applicable
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL HYTRANS G SAE 10W

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Hytrans G SAE 10W	
Product description	Power Shift Transmission Oil	
Product type	Hydraulic Transmission Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -30°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	6.8 to 7.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL HYTRANS G SAE 30W

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Hytrans G SAE 30W	
Product description	Power Shift Transmission Oil	
Product type	Hydraulic Transmission Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	Liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -18°C (ASTM D-97)
Flash point	> 230 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN 4T 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin 4T 20W40	
Product description	Premium Perfomance Four Stroke Engine Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< 21 °C (ASTM D 97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN 4T ADVANCE 10W30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin 4T Advance 10W30	
Product description	Premium Perfomance Four Stroke Engine Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN 4T SCOOL 10W30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin 4T Scool 10W30	
Product description	Premium Perfomance Four Stroke Engine Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN 4T ZOOM 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN 4T ZOOM 20W40	
Product description	Premium Perfomance Four Stroke Engine Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN Q3 10W30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Q3 10W30	
Product description	High Perfomance Motor Cycle Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN Q4 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN Q4 20W40	
Product description	Multigrade Engine Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN Q5 20W50

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spin Q5 20W50	
Product description	High Perfomance Multigrade Motor Cycle Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN X2 20W50

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN X2 20W50	
Product description	High Perfomance Multigrade Motor Cycle Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN X3 10W30

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN X3 10W30	
Product description	Premium Semi Synthetic Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN X4 20W40

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN X4 20W40	
Product description	Premium Semi Synthetic Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPIN X5 15W50

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPIN X5 15W50	
Product description	Premium Semi Synthetic Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SWING SHOCKER OIL

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Swing Shocker Oil	
Product description	Shocker Absorber Oil	
Product type	Motor Cycle Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Brownish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	70 to 75 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL GONDOLA X2

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Gondola X2	
Product description	Engine Oil	
Product type	Outboard Motor Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Greenish
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 50 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	60 to 75 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL GONDOLA X3

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Gondola X3	
Product description	Engine Oil	
Product type	Outboard Motor Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Blue
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 140 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	48 to 52 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPECTRO AX 5W40 SN

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spectro AX 5W40 SN	
Product description	Semi Synthetic Blend Gasoline Engine Oil	
Product type	Passenger Car Motor Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -27°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPECTRO 5W30 SN

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spectro 5W30 SN	
Product description	Semi Synthetic Blend Gasoline Engine Oil	
Product type	Passenger Car Motor Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -27°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPECTRO LX 10W30 SN

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spectro LX 10W30 SN	
Product description	Advanced Passenger Car Motor Oil	
Product type	Passenger Car Motor Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	9.3 to 12.5 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPECTRO SX 20W50 SN

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	DIVYOL SPECTRO SX 20W50 SN	
Product description	HIGH PERFOMANCE GASOLINE ENGINE OIL	
Product type	PASSENGER CAR MOTOR OIL	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -21°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	16.3 to 21.9 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL SPECTRO VX 10W40 SN

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Spectro VX 10W40 SN	
Product description	MULTI GRADE ENGINE OIL	
Product type	PASSENGER CAR MOTOR OIL	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -24°C (ASTM D-97)
Flash point	> 210 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

DIVYOL AUTO PLUS

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	Divyol Auto Plus	
Product description	Multi Grade Diesel Engine Oil	
Product type	Three Wheeler Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-Extreme	Health	1
3-High	Flammability	1
2-Moderate	Reactivity	0
1-Slight	Special	–
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	Distillates (Petroleum) mixture of hydro-treated hydrocarbons	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substance or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection : A half or full-face respirator with filter(s) for organic vapours (and when applicable for H_2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
7.3 Specific end use(s) – Recommendations	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.

Section 8: Exposure Controls / Personal Protection	
The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).	
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume.
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m^3 8 hours. Form: mist and fume STEL: 3 mg/m^3 15 minutes. Form: mist and fume [Air contaminant]
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure control **Appropriate engineering controls**	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properties	
Appearance	Clear
Physical state	liquid
Colour	Red
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	< -3°C (ASTM D-97)
Flash point	> 200 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max @ 15 °C

Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 100 °C (210 °F)	12.5 to 16.3 cst (ASTM D 445)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil substance(s) according to IP346	Not available <3 %

Section 10: Stability and Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H_2S, SO_x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
10.6 Hazardous decomposition products	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate (Petroleum), hydro treated heavy paraffinic	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
	LD 50 Dermal	Rabbit	> 5000 mg/kg	–
	LD 50 Oral	Rat	>15000 mg/kg	–

Irritation / corrosion	
Skin	No known significant effects or critical hazards.
Eye	
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available

Section 12: Ecological Information

12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13: Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 14: Transport Information

International transport regulations

	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN proper shipping name	–	–	–	–
14.3 Transport hazard class(es)	–	–	–	–
14.4 Packing group	–	–	–	–
14.5 Environmental hazards	No	No	No	No
Additional Information	–	–	–	–

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
International Lists National Inventory	**Inventory name**
Australia	Australian Inventory of Chemical Substances (AICS) – Yes
Canada	Domestic Substances List (DSL) – Yes
	Non-Domestic Substances List (NDSL) – No
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes

Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes
	European List of Notified Chemical Substances (ELINCS) – No
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes
Korea	Existing Chemicals List (ECL) – Yes
New Zealand	New Zealand Inventory – Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).	

Section 16: Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good by road.
RID	Regulations agreement concerning the international carriage of dangerous good by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. GANDHAR makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

GANDHAR OIL REFINERY (INDIA) LTD.	
Taloja Plant	Plot No.10, MIDC, Main Road, Taloja, Taluka Panvel, District - Raigad 410208, India.
Silvassa Plant	Plot No. 2, Survey No. 678/1/3, Village Naroli, Near Naroli Check Post, Silvassa, Dadra & Nagar Haveli, Union Territory 396230, India.
Emergency / Info Phone No.	Phone: +91-22-40635600 • Fax: +91-22-40635601
Email	info@gandharoil.com

gandhar
Stay Ahead

Gandhar Oil Refinery (India) Limited
ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, GMP Certified, NABL Accreditation and Government Recognized Three Start Export House

Registered Office
18th Floor, DLH Park, S. V. Road, Goregaon (W), Mumbai 400062, India. | Phone: +91-22-40635600 | Fax: +91-22-40635601
Email: sales@gandharoil.com | Website: www.gandharoil.com

Branch Offices and Depots
Pune | Baroda | Indore | Raipur | Udaipur | Jaipur | Delhi | Faridabad | Ghaziabad | Sonepat | Manesar | Haridwar | Patna | Hyderabad | Mangalore | Bangalore
Guwahati | Varanasi | Hapur | Dharamtar | Jaigarh | Kandla | Surat (Magdalla) | Navlakhi | Krishnapatnam | Vishakapatnam | Gangavaram

Plants
Taloja | Silvassa | Sharjah

July 2021