

DIVYOL ECO4 20W50 API SG / SF

Premium Quality Gas Engine Oil

Applications

Divyol ECO4 20W50 is designed for CNG / LPG fitted cars, taxis, autorickshaws and other three-wheelers fitted with 4-stroke engines. It is blended from premium quality base stocks and selected additives that make the engines perform efficiently despite the high levels of methane and hydrogen sulphide.

Specifications

Divyol ECO4 20W50 meets and exceeds API SG / CF specifications.

Pack Sizes

1 L (HDPE and PET bottles), 3 L, 26 L, 50 L, 210 L.

Advantages

Divyol ECO4 20W50 provides excellent protection against corrosion caused by acid. It also maintains a clean engine by reducing deposits, ensures high oxidation stability and helps avoid unscheduled maintenance.

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	Natural
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	16.3 – 21.9
5	Viscosity index, min.	ASTM D 2270	-	110
6	Flash point, min. COC	ASTM D 92	°C	220
7	TBN, min.	ASTM D 2896	mg KOH/g of oil	6
8	Pour point, max.	ASTM D 97	°C	-9

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.