

DIVYOL GASOL 30 AND 40 API SG / CF

Premium Quality Gas Engine Oils

Applications

Divyol Gasol 30 and 40 are specially formulated for industrial applications with gas engines and gas compressors. They are suitable also for cars, trucks, vans and SUVs running on gas. These engine oils enable consistent performance from these machines and vehicles.

Specifications

Divyol Gasol 30 and 40 are blended using premium quality base stocks and additives and generate less than 0.5% ash content. They meet and exceed OEM specifications and are specially recommended for vehicles manufactured by Caterpillar, MWM, Perkins, Wartsila, Cummins, GEJENBACHER, MAN, WAUKESHA (APG), etc.

Pack Sizes

1 L (HDPE and Pet bottle), 3 L, 26 L, 50 L, 210 L.

Advantages

Divyol Gasol 30 and 40 provide excellent lubrication, piston cleanliness, superior control over deposit, high oxidation stability and protection against rust to engine internals. They also help extend the service life of the valve and spark plug.

Sr. No.	Characteristics	Test Method	UOM	Gasol 30	Gasol 40
1	Appearance	Visual	-	Bright and clear	Bright and clear
2	Colour, max.	ASTM D 1500	-	Natural	Natural
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report	To report
4	Kinematic viscosity at 40 °C	ASTM D 445	cSt	To report	To report
5	Kinematic viscosity at 100 °C	ASTM D 445	cSt	9.3 – 12.5	12.5 – 16.3
6	Viscosity index, min.	ASTM D 2270	-	110	110
7	Flash point, min. COC	ASTM D 92	°C	220	220
8	TBN, min.	ASTM D 2896	mg KOH/g of oil	5	5
9	Pour point, max.	ASTM D 97	°C	-3	-3
10	Ash content	ASTM D 482	%	0.5	0.5

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.