

## DIVYOL SCREW PRESS 32 / 46 / 58 COMPRESSOR OILS

### Applications:

Divyol Screw Press Compressor Oils are carefully formulated blends for the lubrication of severe duty reciprocating and rotary air compressors with air discharge temperature up to 220 °C. This blend of oils is designed to endure high temperatures. Regular use has been found to significantly reduce the oil change frequency as compared to HLP level products used by the industry.

### Standards:

Divyol Screw Press Compressor Oils meet the performance specifications of most OEMs as also of DIN 51524 PART-II, DIN 51506 VD-L GROUP, DIS 6521 and Cincinnati Milacron P- 68, P-69 and P-70.

### Advantages:

The use of Divyol Screw Press Compressor Oils results in longer oil change intervals and effective protection to machine internals. This helps in reducing the cost and requirement of machine maintenance.

### Typical properties:

Sr. No.	Characteristics	Test Method	Divyol Screw Press		
			32	46	68
1	Appearance	Visual	Bright and clear	Bright and clear	Bright and clear
2	Colour, max.	ASTM D 1500	1	1	1
3	Kinematic viscosity at 40 °C, cSt min.	ASTM D 445	32	46	68
4	Flash point, COC, °C, min.	ASTM D 92	200	210	220
5	Pour point, °C, max.	ASTM D 97	-9	-9	-9
6	Copper corrosion	ASTM D 130	1	1	1
7	Rust prevention	ASTM D 665 A/B	Complies	Complies	Complies
8	FZG failure load stage, min.	ASTM D 5182	9	9	9

The above properties are typical values and do not constitute specification of the product.

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.