



DIVYOL SPECTRO LX 10W30 SN Advanced Passenger Car Motor Oil

Applications

Divyol Spectro LX 10W30 SN is an advanced blend of motor oil for most models of modern high output turbo charged gasoline engines, such as passenger cars, sport utility vehicles, vans, and light duty trucks. It is also a good choice for vehicles running on upto 85% ethanol-blended fuels.

Specifications

Divyol Spectro LX 10W30 SN is blended using premium quality base stock and select additives. It meets and exceeds performance standards as per API SN.

Pack Sizes

1L, 3L, 3.5 L, 26L, 50 L, 210 L.

Advantages

Divyol Spectro LX 10W30 SN provides excellent protection against sludge and wear for a long period, as well as lubrication over a wide range of temperatures. It helps maintain cleanliness of critical components like piston, turbo-charger and seal. Fuel economy gets maximized; so does oil consumption, leading to less frequent oil changing.

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	Natural
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	9.3 –12.5
5	Viscosity index, min.	ASTM D 2270	-	130
6	Flash point, min. COC	ASTM D 92	°C	215
7	TBN, min.	ASTM D 2896	mg KOH/g of oil	7
8	Pour point, max.	ASTM D 97	°C	-24

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.

