

# DIVYOL SPINE SXD XD 90, 75W90, 80W90 API GL5

## Heavy Duty Premium Gear Oils

### Applications

Divyol Spine GL5 is a series of heavy duty gear oils suitable for a wide range of commercial fleet, mechanical transmissions, gear boxes and axles, especially in very demanding operating conditions. This special blend is also recommended for hypoid and bevel gears in rear axles of vehicles and gear boxes.

### Specifications

Divyol Spine GL5 gear oils meet and exceed OEM performance levels, including API GL5, IS:1118:1992 (EP Type GL-5) and US MIL-L-2105D.

### Pack Sizes

500ml, 1 L, 5 L, 10 L, 20 L, 26 L, 50 L, 210 L

### Advantages

Divyol Spine GL5 heavy duty gear oils provide excellent lubrication under severe operating conditions. They ensure the highest protection against wear and corrosion, enable easy gear shifting, especially at very low temperatures, and can withstand high bulk oil temperatures. These qualities help in extending service life of the engine and components.

Sr. No.	Characteristics	Test Method	UOM	Spine SXD 75W90 GL5	Spine XD 80W90 GL5	Spine_XD90
1	Appearance	Visual	-	Bright and clear	Bright and clear	Bright and clear
2	Colour, max.	ASTM D 1500	-	5	5	5
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report	To report	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	14 – 16	14 – 18	14 – 18
5	Viscosity index, min.	ASTM D 2270	-	100	90	90
6	Flash point, min. COC	ASTM D 92	°C	180	195	195
7	Pour point, max.	ASTM D 97	°C	-33	-9	-6

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.