



DIVYOL SPINE SXP 75W90 API GL4 – API GL4, SYNTH BLEND

Multi-purpose Extreme Pressure Gear Oil

Applications

Divyol Spine SXP 75W90 is ideal for gear boxes requiring extreme pressure properties such as hypoid and bevel gears. It is recommended for passenger cars, buses, highway trucks and worm gear axles, especially where API GL-4 gear oil is recommended. It is also suitable for manual transmission of automobiles and rear axles.

Specifications

Divyol Spine SXP 75W90 gear oil meets and exceeds OEM specifications such as API GL4, IS:1118:1992 (EP Type GL-4) and MIL-L-2105.

Pack Sizes

500 ml, 1 L, 5 L, 10 L, 20 L, 26 L, 50 L, 210 L.

Advantages

Divyol Spine SXP 75W90 provides excellent lubrication under severe operating conditions. They ensure the highest protection against wear and corrosion, and also enable easy gear shifting, especially at very low temperatures. These qualities help in extending service life of the engine and components.

Sr. No.	Characteristics	Test Method	иом	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	5
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	14 – 16
5	Viscosity index, min.	ASTM D 2270	-	100
6	Flash point, min. COC	ASTM D 92	∘C	180
7	Pour point, max.	ASTM D 97	∘⊂	-33

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.

