



DIVYOL TQX-1 Hydraulic Transmission Fluid

Applications

Divyol TQX-1 automatic transmission fluid is specially developed for light vehicles that have modern automatic transmission and power steering units.

Specifications

Divyol TQX-1 automatic transmission fluid is blended from premium quality base stocks and advanced additives. It meets performance specifications of General Motor's automatic transmission fluid Type 'A' Suffix 'A', as well other OEM specifications.

Pack Sizes

500 ml, 1 L, 5 L, 26 L, 50 L, 210 L.

Advantages

Divyol TQX-1automatic transmission fluid has the required friction characteristics for a smooth transmission performance. It also has excellent anti-oxidation, dispersancy, anti-wear and de-foaming properties. These qualities ensure complete and effective protection, especially to the critical and complex transmission components.

Sr. No.	Characteristics	Test Method	UOM	Specifications
1	Appearance	Visual	-	Bright and clear
2	Colour, max.	ASTM D 1500	-	Red
3	Specific gravity at 29.5 °C	ASTM D 1298	-	To report
4	Kinematic viscosity at 100 °C	ASTM D 445	cSt	7 – 8.5
5	Viscosity index, min.	ASTM D 2270	-	150
6	Flash point, min. COC	ASTM D 92	∘⊂	180
7	Pour point, max.	ASTM D 97	°C	-39

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.

