

DIVYOL CLEANING SOLUBLE OILS DG / DH

Applications:

Divyol Cleaning Soluble Oils DG and DH are water-based cleaning fluids specially formulated for use wherever mineral turpentine and kerosene are not available. These fluids are recommended for use on all metal components whose surfaces need to be cleaned, especially micro-finished parts, after machining and before they become part of sub-assemblies or before being treated with rust preventive oils.

Advantages:

Divyol Cleaning Soluble Oils DG and DH work efficiently on both ferrous and non-ferrous metal components and machine assemblies. Since the formulation is a water-based cleaning agent, it is to be mixed with water in a required proportion depending upon the application. With super cleaning capability, it effectively removes oils and greases from metal surfaces, reduces cycle time of operations, improves productivity of cleaning operations, makes machines more productive and proves to be cost effective.

Typical properties:

Sr. No.	Characteristics	Test Method	Divyol DG Cleaner	Divyol DH Cleaner
1	Colour, max.	ASTM D 1500	1.0	1.0
2	Appearance	Visual	Bright and clear	Bright and clear
3	Flash point, COC, °C, min.	ASTM D 92	40	42
4	Pour point, max.	ASTM D 97	<-3	<-3
5	Kinematic viscosity at 40 °C, min.	ASTM D 445	2 – 5	2 – 5
6	Emulsion type	–	Milky White	Milky White
7	pH of 5 % emulsion	ASTM R70 / 97	5.9	6.3

The above properties are typical values and do not constitute specification of the product.

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.